

日東コン 材質 M (チタン酸マグネシウム系) 規格表

形式名	端子構造	公称 静電容量 pF±10%	定格電圧		定格 KVA (1MHz)		最大値			寸法 (mm)			備考
			50°C kV _{DC}	70°C kV _{DC}	50°C	70°C	HF kV	電流 [A]		D ±10%	T ±3	H ±3	
								50°C	70°C				
MDF160A-S	S	300	42	38	225	150	36	34	28	160	22.5	48.0	
MDF160A-S	S	350	42	38	225	150	36	35	29	160	21.0	47.0	
MDF160A-S	S	400	36	38	225	150	27	36	30	160	20.5	46.0	
MDF160A-S	S	500	30	28	225	150	22.5	38	31	160	19.0	45.0	
MDF140A-S	S	100	37	34	135	90	31.5	22	18	140	26.0	52.0	
MDF140A-S	S	150	37	34	135	90	31.5	24	20	140	22.0	48.0	
MDF140A-S	S	200	32	28	135	90	27	27	22	140	21.0	47.0	
MDF140A-S	S	250	32	28	135	90	27	28	23	140	19.5	46.0	
MDF110A-S	S	100	26	24	67.5	45	22.5	17	14	110	24.5	50.0	
MDF110A-S	S	150	26	24	67.5	45	22.5	18	15	110	21.5	47.0	
MDF110A-S	S	200	26	24	67.5	45	22.5	19	16	110	20.0	45.0	
MDF80A-S	S	100	19	17	30	20	16	13.5	11	80	20.0	30.0	
MDF80A-S	S	150	19	17	30	20	16	14.5	12	80	18.5	28.5	
MDF80A-S	S	170	19	17	30	20	16	14.5	12	80	18.0	28.0	
MDF60A-S	S	50	14	12	15	10	11	8.5	7	60	17.0	25.0	
MDF60A-S	S	100	14	12	15	10	11	9.5	8	60	15.0	23.0	
MD110A-S	S	100	17	15	30	20	4	13.5	11	110	6.0	31.0	
MD110A-S	S	150	17	16	15	10	4	15	12	110	4.3	29.3	
MD110A-S	S	200	17	16	15	10	4	16	13	110	4.3	29.3	
MD110A-S	S	250	17	16	15	10	4	16	13	110	4.3	29.3	
MD110A-S	S	300	17	16	15	10	4	17	14	110	3.8	28.8	
MD80A-S	S	100	16	15	15	10	4	11	9	80	5.0	29.0	
MD80A-S	S	150	16	15	15	10	4	12	10	80	3.5	27.5	
MD80A-S	S	200	15	15	15	10	4	13	11	80	3.0	27.0	
MD60A-S	S	50	12	11	7.5	5.0	4	7	6	60	5.0	25.0	
MD60A-S	S	70	12	11	7.5	5.0	4	7	6	60	5.0	25.0	
MD60A-S	S	100	12	11	7.5	5.0	4	8	7	60	3.0	23.5	
MD40A-S	S	20	12	11	3.8	2.5	4	5	4	40	4.2	24.2	
MD40A-S	S	30	12	11	3.8	2.5	4	5	4	40	4.2	24.2	
MD40A-S	S	50	11	10	3.8	2.5	4	6	5	40	2.8	22.8	