

## 日東コン 材質 R (酸化チタン系) E 型 規格表

形式名	端子構造	公称 静電容量 pF±10%	定格電圧		定格 KVA (1MHz)		最大値			寸法 (mm)			備考
			50°C kV <sub>DC</sub>	70°C kV <sub>DC</sub>	50°C	70°C	HF kV	電流 [A]		D ±10%	T ±3	H ±3	
								50°C	70°C				
RE-110	S	400	11	8.5	10	6.5	2	13.5	11	110	7.0	32.0	
RE-110	S	500	11	8.5	10	6.5	2	14.5	12	110	7.0	32.0	
RE-110	S	600	11	8.5	10	6.5	2	16	13	110	7.0	32.0	
RE-110	S	700	11	8.5	10	6.5	2	16	13	110	7.0	32.0	
RE-110	S	800	8.5	7.0	10	6.5	2	17	14	110	4.0	29.0	
RE-110	S	1000	8.5	7.0	10	6.5	2	17	14	110	3.5	28.5	
RE-110	S	1200	6.0	5.0	10	6.5	2	18.5	15	110	3.5	28.5	
RE-110	S	1500	6.0	5.0	10	6.5	2	19.5	16	110	2.5	27.5	
RE-110	S	2000	6.0	5.0	10	6.5	2	21	17	110	2.5	27.5	
RE-80	S	300	8.5	7.0	7	4.5	2	11	9	80	5.0	29.0	
RE-80	S	400	8.5	7.0	7	4.5	2	12	10	80	5.0	29.0	
RE-80	S	500	8.5	7.0	7	4.5	2	13.5	11	80	4.4	28.4	
RE-80	S	600	8.5	7.0	7	4.5	2	13.5	11	80	4.4	28.4	
RE-80	S	700	7.0	5.5	7	4.5	2	14.5	12	80	2.2	26.2	
RE-80	S	800	7.0	5.5	7	4.5	2	14.5	12	80	2.2	26.2	
RE-80	S	1000	7.0	5.5	7	4.5	2	16	13	80	2.1	26.1	
RE-80	S	1200	6.0	5.0	7	4.5	2	16	13	80	1.8	25.8	
RE-80	S	1500	6.0	5.0	7	4.5	2	17	14	80	1.5	25.5	
RE-60	S	200	7.0	5.5	5	3.5	2	8.5	7	60	4.5	24.5	
RE-60	S	250	7.0	5.5	5	3.5	2	9.5	8	60	4.5	24.5	
RE-60	S	300	7.0	5.5	5	3.5	2	9.5	8	60	4.5	24.5	
RE-60	S	400	6.0	5.0	5	3.5	2	11	9	60	2.8	22.8	
RE-60	S	500	6.0	5.0	5	3.5	2	11	9	60	2.8	22.8	
RE-60	S	600	6.0	5.0	5	3.5	2	12	10	60	2.4	22.4	
RE-60	S	700	5.0	4.0	5	3.5	2	12	10	60	2.4	22.4	
RE-60	S	800	5.0	4.0	5	3.5	2	12	10	60	1.8	21.8	
RE-60	S	1000	5.0	4.0	5	3.5	2	12	11	60	1.8	21.8	
RE-50	S	100	6.0	5.0	4	2.8	2	6.5	5.5	50	7.5	27.5	
RE-50	S	150	6.0	5.0	4	2.8	2	8	6.5	50	7.5	27.5	
RE-50	S	200	6.0	5.0	4	2.8	2	8	6.5	50	4.0	24.0	
RE-50	S	250	6.0	5.0	4	2.8	2	9	7.5	50	4.0	24.0	
RE-50	S	300	6.0	5.0	4	2.8	2	9	7.5	50	4.0	24.0	
RE-50	S	400	5.0	4.0	4	2.8	2	10	8	50	2.2	22.2	
RE-50	S	500	5.0	4.0	4	2.8	2	10	8	50	2.2	22.2	
RE-50	S	600	5.0	4.0	4	2.8	2	11	9	50	2.2	22.2	
RE-40	S	50	5.0	4.0	3	2	2	6	5	40	6.5	26.5	
RE-40	S	100	5.0	4.0	3	2	2	6	5	40	6.5	26.5	
RE-40	S	150	5.0	4.0	3	2	2	7	6	40	3.0	23.0	
RE-40	S	200	5.0	4.0	3	2	2	7	6	40	3.0	23.0	
RE-40	S	250	5.0	4.0	3	2	2	8.5	7	40	2.5	22.5	
RE-40	S	300	5.0	4.0	3	2	2	8.5	7	40	2.5	22.5	
RE-40	S	400	3.5	2.8	2.2	1.5	2	8.5	7	40	1.5	21.5	
RE-40	S	500	3.5	2.8	2.2	1.5	2	8.5	7	40	1.5	21.5	
RE-30	S	50	5.0	4.0	2	1	2	5	4	30	5.5	25.5	
RE-30	S	100	5.0	4.0	2	1	2	5	4	30	3.2	23.2	
RE-30	S	150	5.0	4.0	2	1	2	6	5	30	2.0	22.0	
RE-30	S	200	5.0	4.0	2	1	2	6	5	30	2.0	22.0	
RE-30	S	250	3.0	2.5	2	1	2	6	5	30	1.7	21.7	
RE-30	S	300	3.0	2.5	2	1	2	6	5	30	1.7	21.7	
RE-30	S	400	2.0	1.5	1	0.7	1	6	5	30	1.0	21.0	
RE-30	S	500	2.0	1.5	1	0.7	1	6	5	30	1.0	21.0	
RE-20	S	50	3.0	2.5	1.5	1	2	3	2.5	20	3.3	19.3	
RE-20	S	100	3.0	2.5	1.5	1	2	3	2.5	20	2.0	18.0	
RE-20	S	150	2.0	1.5	1.5	1	2	4	3.0	20	1.2	17.2	
RE-20	S	200	2.0	1.5	1.5	1	2	4	3.0	20	1.0	17.0	